

Series	Light Engine	Current	Nominal Power	Voltage	Mounting	Optic	CCT	Colour	Control Options	
B BALDER	A Standard Short	A 350mA	80 80W	L 100-277VAC	D Surface	T2M T3S	30K 3000K	BK Black-RAL9011	DIM	1-10V Dimming
L LINK	B Standard Long	B 530mA	...	H 277-480VAC	J J Tunable	T3M T4VS	40K 4000K	WH White-RAL9010	PWM	10V PWM Control
P POLESTAR	C High Power Short	C 700mA			L L Tunable	T4S T4M	50K 5000K	GY Gray RAL-7004	DALI	DALI Control
R ROMA	D High Power Long	D 1050mA			T T Fix	T5M(120°) T5W(150°)	57K 5700K	BZ Bronze RAL-8019	DMX	DMX512 Control
S	E Integrated Single	E 1400mA			U U Adjustable	T10D T25D	GRE green	GN (sur-mesure) Green-	MMS	Microwave Motion Sensor
SP SKYLINE	F Integrated Double	F 1750mA				T40D T60D	AMB amber	BU(sur-mesure) Blue-	EPS	Emergency Power Supply
W WILA	G Integrated Triple	G 2100mA				T90D	RED red	OG(sur-mesure) Orange-	PC3	Photocell 3pin Receptacle+Photocell Sensor
	M Medium power	L <350mA					BLU blue		PC7	Photocell 7pin Receptacle+Photocell Sensor
<p>10 years warranty by default.</p> <p>10KA SPD parallel by default; 20KA SPD series can be customized.</p> <p>1900K (AMB - amber) same price as 3000K; other CCT can be customized.</p> <p>CRI 70 by default; CRI 80 optional with loss of luminosity 6 - 10%.</p> <p>CRI 90 can be customized.</p> <p>Gray RAL7004 by default; Black RAL9011, White RAL9010 and Bronze RAL8019 optional.</p> <p>Other housing colors can be customized.</p>									PCM	Photocell Mini Sensor
									BLS	Back Light Shield
									BSP	Bird Spike
									SAC	Safety Cable
									ORL	Optics Rotated Left
									ORR	Optics Rotated Right
									CMS	Customized Solutions